

BF-AP5016

Analog Two-Way Radio

BF-AP5016, the new generation high power analog two-way radio, can adapt multi-scenes for its many outstanding advantages in many aspects like modern design, strong signal penetration, long battery life, excellent sound quality, drop resistance and compression ability, etc., guaranteeing continuity and reliability effectively.

- VOX
- High Power
- Squelch Level
- Channel Matching
- Type-C Charging Mode
- Busy Channel Locking
- Special Signal Mode
- O Noise Reduction(Optional)







SPECIFICATION

General		
Frequency Range	UHF: 400-480MHz	
Channel Capacity	16	
Channel Spacing	25 KHz /12.5 KHz	
Frequency Stability	≤ ± 2.5 ppm	
Antenna Impedance	50 Ω	
Operating Voltage	DC 7.4V (±20%)	
Battery Capacity	1800mAh	
RF Output Power	≤5W	
Dimensions (L \times W \times H)	54* 33* 113mm	
Weight	214g	
Transmitter		
4FSK Modulation	11K ф F3E/16K ф F3E	
FM Modulation	≤ ± 2.5KHz / ± 5.0KHz	
Adjacent Channel Power	60dB	

Receiver		
Sensitivity	≤-122dBm (12dB SINAD)	
Intermodulation	≥60dB(Wide)/ 55dB (Narrow)	
Adjacent Channel Selectivity	≥60dB(Wide)/ 55dB(Narrow)	
Spurious Response Rejection	≥60dB(Wide)/ 55dB(Narrow)	
Rated Audio Output Power	0.5W	
Audio Distortion	≤5%	

Environmental		
Operating Temperature	-20°C ~ +60°C	
Storage Temperature	-30℃ ~+70℃	

- 1. Due to continuous product improvement, the technical parameters and functional features may not be consistent with the actual product. Please refer to the actual product. If there is any change, we will not notify you separately. Please understand.
- 2. If you have other questions about this product or the content of this document is not detailed enough, please contact us.

ACCESSORIES



Audio Distortion













Fujian BelFone Communications Technology Co., Ltd

Add: A-15 Huaqiao Economic Development Zone, Luojiang, Quanzhou, Fujian, China Email: overseas@belfone.com

Phone: +86 595 28396717 Fax: +86 595 22771635









BelFone







